














Item No.	Product name	Picture	Specification(mm)	Weight(kg)	Steel material	Zinc coating thickness
1	Hot dip galvanized W beam Guardrail		4318*310*85*3.0	49.16	Q235B/Q355B	550g/m ²
			4318*310*85*2.75	45.06	Q235B/Q355B	
			4318*310*85*2.5	40.96	Q235B/Q355B	
			4128*310*85*3.0	46.97	Q235B/Q355B	
			4128*310*85*2.75	43.06	Q235B/Q355B	
			4128*310*85*2.5	39.15	Q235B/Q355B	
3504*310*85*2.75	36.55	Q235B/Q355B				
2	Powder Spray W beam guardrail		4310*310*83*2.75mm	45.06	Q235B/Q355B	550g/m ²
3	Curved W/Thrie beam Guardrail		As your request (Customized)		Q235B/Q355B	550g/m ²
4	Hot dip galvanized highway Thrie beam guardrail		4318*506*85*2.75	70.1	Q235B/Q355B	550g/m ²
5	Highway guardrail two waves transform three waves		2320*506*310*2.75	35	Q235B/Q355B	550g/m ²
6	155 highway guardrail		4316*155*42*3.0	22.5	Q235B/Q355B	550g/m ²
7	Bridge Guardrail		As your request (Customized)		Q235B	550g/m ²
8	Pedestrian Fencing		Height:870 Length:2000/2500/3000 As your request	35	Q235B	550g/m ²
9	"U" Guardrail post		150*75*5*L	11.38/m	Q235B/Q355B	550g/m ²
			178*76*6*L	14.98/m	Q235B/Q355B	550g/m ²
			150*100*5*L	13.35/m	Q235B/Q355B	550g/m ²
10	"U"Guardrail flange post		150*75*5*750 / 300*300*10	15.6	Q235B/Q355B	550g/m ²
			150*75*5*750 / 200*200*10	11.67	Q235B/Q355B	550g/m ²
			178*76*6*750 / 300*300*10	18.3	Q235B/Q355B	550g/m ²

11	Guardrail "U" spacer		150*75*5*360	4.1	Q235B/Q355B	350g/m ²
			178*76*6*360	5.39	Q235B/Q355B	350g/m ²
12	Guardrail "H" post		150*100*4.5*5.5*Length	13.5/m	Q235B/Q355B	550g/m ²
13	"H" Guardrail flange post		150*75*748 / 250*330*12	18.46	Q235B/Q355B	550g/m ²
			150*75*548 / 250*330*12	15.6	Q235B/Q355B	550g/m ²
14	"Z" Guardrail post		100*50*4*Length	6.3/m	Q235B/Q355B	550g/m ²
			125*90*4*Length	10.2/m	Q235B/Q355B	550g/m ²
15	"Z" Guardrail flange post		100*50*4*750 / 200*200*10	7.86	Q235B/Q355B	550g/m ²
			125*90*4*750 / 200*200*10	10.8	Q235B/Q355B	550g/m ²
16	EZYGuard Z post		1650/1600*90*50*4.5/4.3	13.9	Q235B	550g/m ²
17	"C" Guardrail post		120*55*16*4*Length	7.724/m	Q235B/Q355B	550g/m ²
			150*110*32*4.3*Length	14.07/m	Q235B/Q355B	550g/m ²
18	Sigma guardrail post		100*55*16*4*Length	7.65/m	Q235B/Q355B	550g/m ²
19	Spring Steel Buffas		76*610*10	10	Q235B/45Mn	550g/m ²
20	Steel Bollards on Baseplate		As your request (Customized)		Q235B/Q355B	
21	Guardrail Box Spacer		334*194*90*3	3	Q235B/Q355B	350g/m ²

22	Guardrail Octangle Spacer		200*203*100*3	3	Q235B/Q355B	350g/m ²
23	Fishtail (two waves)		700*310*2.75	8.5	Q235B/Q355B	350g/m ²
24	Fishtail (three waves)		700*506*2.75	12.5	Q235B/Q355B	350g/m ²
25	Fishtail (two waves)		760*310*2.75	9.25	Q235B/Q355B	350g/m ²
26	Fishtail (three waves)		760*506*2.75	13.5	Q235B/Q355B	350g/m ²
27	W beam bullnose end		R159*610*406*2.75mm	8	Q235B	550g/m ²
28	90°corner End		445*445*2.75	8.5	Q235B/Q355B	350g/m ²
29	135°corner End		600*600*2.75	12.5	Q235B/Q355B	350g/m ²
30	PED guardrail terminal end		∅ 75*101*320	7.5	Q235B/Q355B	350g/m ²
31	Open box		200*150*5*4805	89.5	Q235B/Q355B	350g/m ²
32	Hydraulic support		100*100*5658	180	Q235B/Q355B	550g/m ²

33	W beam Guardrail End Terminals		Highway Guardrail W beam: 4128*310*83*2.75	43.06	Q235B	550g/m ²
			Buffer end:500*600*1800	85		
			Guardrail post 1: 150*100*780	39		
			Guardrail post 2: 150*100*1250			
			Support the square tube: 100*50*4*1900	16.82		
			Cable stay support assembly	28.5		
34	Crash Cushion		R275*406*2.75	19	Q235B	550g/m ²
			As your request (Customized)	200	Q235B	550g/m ²
						
34	Crash Cushion		3250*1135*850 4000*1135*850 6490*1135*850 (With impact test report)	460/560/860	Q235B	550g/m ²
35	Reflector		Color Customized	0.25		
36	Bolts & Nuts		M16*35	0.14	8.8	
			M16*45	0.15	8.8	
			M16*50	0.16	8.8	
37	Washer(Round;Square)		76*44	0.1		
38	Crash barrier Sleeve		150mm length Or Customized/Follow the Crash barrier Specs Color: Traffic yellow	0.75		
39	All kinds of Guardrail post Sleeve		50mm length Color: Traffic yellow	0.35		